## Toluene Diisocyanate (TDI 80/20) in IRAN



M/s. Bimal Pharma Pvt. Ltd., Mumbai, India e: info@bimalpha.com / info@nisinindia.com

Mob.: 0091- 9702968181 / 9322591096



**Toluene Diisocyanate:** We offer it as Clear Colourless to Yellowish Liquid with Purity 99.7% & above.

Introduction: HS Code No.: 29291010 Odor: Sharp, Pungent Odor

Toluene Diisocyanate : CAS No. 26471-62-5
2,4-Toluene Diisocyanate : CAS No. 584-84-9
2,6-Toluene Diisocyanate : CAS No. 91-08-7

• TDI (Toluene Diisocyanate) is an Organic Compound, produced from Toluene, followed by Phosgenation.

• It is a mixture of Two, Commercially Important, Isomers, 2,4-TDI (80%) and 2,6-TDI (20%).

• It is used in production of Rigid & Flexible Polyurethane Foams, with High Temp. Stability.

• Also used in making Urethane Paints, Varnishes, Elastomers & Coatings.

**Specification:** Most Stringent Quality controlled Product.

Assay (Purity)
99.90% Min.
Total Acidity
40 ppm Max.

Hydrolyzable Chlorine : 80 ppm Max.
 Total Chlorine : 700 ppm Max.

• Isomer Content (%) • Colour (APHA) : 25 Max.

2,4- Toluene Diisocyanate :  $80\pm1$ 2,6- Toluene Diisocyanate :  $20\pm1$ 

## **Major Applications:**

In the manufacturing of Polyurethane Resins being used across a Vast Range of Industries, like:

• Apparel: To produce Stretchable, Lightweight Fabrics.

• Appliances: For Thermal Insulation in Refrigerators & Freezers etc.

• Automotive: For Car Seats, Car Ceiling, Body, Doors, Windows, Bumpers, Spoilers etc.

• Construction : Foam-core panels.

Composite Wood: To make Cabinets & other Furniture in Homes.

Electronics: For Sealing, Compressing & Insulating Circuit Boards.

• Flooring & Furnishings: To make more Sturdier Floors, (Bedding & Carpet Padding).

• Marine: To improve Durability & Sturdiness of Boats.

• Medical: Mainly in Equipment's & Accessories

E.g.: Surgical Drapes, Injection Molded Devices, Wound Dressing etc.

• Packaging: PU Packing Foam allows to Secure & Protect Goods throughout Transit period

(Classware Medical Equipment etc.)

(Glassware, Medical Equipment etc.)

Paints

Packings : 250 Kgs. Net in new Steel Drums

: In 20 ft. FCL, 20 MT Palletized